



# PrimeGuard

## PrimeGuard



PrimeGuard conditions the surface by displacing any moisture.

**Description:** PrimeGuard is a formulation of petroleum based waxes, plasticizers, and moisture displacing corrosion inhibiting compounds. PrimeGuard will not dry out, harden or crack and is applicable for dry or wet surfaces. PrimeGuard conditions the metal structure by displacing any surface moisture. This provides SCC Wax Wraps with a surface that allows it to protect the metal structure to its fullest potential. PrimeGuard is offered in above and belowground grades.

**Application Procedure:** To prepare the surface remove all loose scale, rust, paint, and other foreign material. With gloved hand, apply a thin layer of SCC PrimeGuard to all areas of the metal structure that is to be wrapped with SCC's Wax Wraps. Extend the primer a minimum 6 inches beyond the area to be wrapped with SCC's Wax Wraps. Wraps may be applied immediately following application of PrimeGuard.

## PrimeGuard 250



PrimeGuard 250 requires minimal surface preparation.

**Description:** PrimeGuard 250 is a formulation of petroleum based waxes, plasticizers, and moisture displacing corrosion inhibiting compounds. PrimeGuard 250 is a Non-Melting primer designed to be used as a surface conditioner for above and belowground applications with high ambient temperatures and hot surfaces. PrimeGuard 250 will not dry out, harden, melt, or crack.

**Application Procedures:** To prepare the surface remove all loose scale, rust, paint, and other foreign material. With gloved hand, apply a thin layer of SCC PrimeGuard 250 to all areas of the metal structure that is to be wrapped with SCC's Wax Wraps. Extend the primer a minimum 6 inches beyond the area to be wrapped with SCC's Wax Wraps. Wraps may be applied immediately following application of PrimeGuard 250.



# PrimeGuard

## PrimeGuard

### Advantages:

- Only minimal surface preparation required
- Easy to apply by hand
- No curing time necessary for immediate service
- Environmentally safe, non toxic, no VOC's
- No clay fillers
- Excellent wetting properties

### Technical Data:

Properties	Specifics
Color	White, Brown
Flash Point	>390°F
Coverage	100 ft <sup>2</sup> /gallon

### Packaging:

1 gallon pail	4-1 gallon pails/case
---------------	-----------------------

## PrimeGuard 250

### Advantages:

- Only minimal surface preparation required
- Non-Melting
- No curing time necessary for immediate service
- Environmentally safe, non toxic, no VOC's
- Easy to apply by hand

### Technical Data:

Properties	Specifics
Color	Brown
Flash Point	>390°
Melting Point	Non-Melting
Coverage	100 ft <sup>2</sup> /gallon

### Packaging:

1 gallon pail	4-1 gallon pails/case
---------------	-----------------------