



SCC Pro Mold Putty



Description: Petroleum based anticorrosive filling compound that provides the ability to mold irregular surfaces for an even application of SCC's Wax Wrap.

Application Procedure: To prepare the surface remove all loose scale, rust, paint, and other foreign material. By hand, apply SCC Pro Mold Putty to the surface. Press and mold the material onto the surface ensuring the putty is wetting and adhering. Continue working SCC Pro Mold Putty to the area until desired profile is achieved. Once desired profile is achieved, finish by overwrapping with SCC's Wax Wraps.

Features:

- Only minimal surface preparation is required
- Easily conforms to irregular surfaces
- No curing time needed for immediate service
- Environmentally safe, non-toxic, no VOC's
- Will not dry out in heavy clay soils
- Applied over wet or dry surfaces

Technical Data:

Properties	English
Color	Gray
Specific Gravity	1.11
Maximum Service Temperature	200°F
Flash Point	>350°F

Packaging:

2-gallon pails.....Sold Individually



201 Andrew Park Drive
Jackson, Michigan 49202
Phone: 1-517-748-9330
Fax: 1-517-784-9331
www.superiorcorrosioncontrol.net

We believe the information on this sheet to be reliable and accurate but do not guarantee. The information on this sheet is intended as a general guide for product selection only and should not be used for specification purposes. Before using, user by their own test should determine the suitability of the product and information supplied by us for their own purposes.